

SAFETY DATA SHEET

1. IDENTIFICATION

Product identifier used on the label

: **Flottec 4277 Collector**

Recommended use of the chemical and restrictions on use

: Collector used in mining industry

Chemical family

: Thionocarbamate

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:

Flottec, LLC

338 West Main Street
Boonton, NJ 07005 U.S.A.
www.flottec.com

Information Telephone # : (973) 588 4717

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.)

2. HAZARDS IDENTIFICATION

Classification of the chemical



H302: Harmful if swallowed

H319: Causes eye irritation

H315: Causes skin irritation

H336: May cause drowsiness or dizziness

Flammable liquids (Category 4)
Serious toxicity, oral (Category 4)
Skin corrosion / irritation (Category 2)
Eye Damage / Irritation (Category 2)
Specific target organ toxicity, single exposure, narcotic effects (Category 3)

Label elements

Signal Word

Danger

Hazard statement(s)

H227: Combustible liquid
H302: Harmful if swallowed
H319: Causes eye irritation
H315: Causes skin irritation
H336: May cause drowsiness or dizziness.
H412: Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P260: Do not breathe mist, vapors and spray.
P264: Wash face, hands and any exposed skin thoroughly after handling.
P280: Wear protective gloves, protective clothing and eye protection.
P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
P363: Wash contaminated clothing before reuse.

- P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P310: Immediately call a POISON CENTER or doctor/physician.
- P405: Store locked up.
- P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Common name	CAS #	Concentration / wt %
Sodium diethyl phosphorodithioate	3338-24-7	20 – 70
Ethyl Isopropyl Thionocarbamate	141-98-0	5 – 30
Isopropyl alcohol	67-63-0	2 – 20
Potassium hydroxide	1310-58-3	2 -5

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If spontaneous vomiting occurs, keep head below hips level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink.
- Inhalation* : Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
- Skin Contact* : Flush with water for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. Seek medical attention immediately.
- Eye Contact* : IMMEDIATELY flush with plenty of water. Remove contact lenses. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention. Seek medical attention immediately.

Symptoms : May cause severe eye irritation or eye damage. May cause skin irritation and burns. May cause burns to mouth, throat and stomach.

Notes to the physician : Treat according to person's condition and specifics of exposure. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIRE-FIGHTING MEASURES

Extinguishing media

- Suitable extinguishing media* : Dry chemicals, water spray, chemical foam, carbon dioxide (CO₂).
- Unsuitable extinguishing media* : Do not use direct water jet.

Special hazards arising from the substance or mixture

: This product is an aqueous solution which does not support combustion unless the water has been evaporated. Emits toxic and corrosive fumes under fire conditions.

Special protective equipment and precautions for firefighters

- Protective equipment for fire-fighters* : Firefighters must wear self-contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
- Special fire-fighting procedures* : Use water spray to cool fire-exposed containers. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.

Environmental precautions

: Prevent entry in sewer and other enclosed area. For a large spillage, consult the Department of Environment or the relevant authorities.

Methods and material for containment and cleaning up

: Ventilate the area well. Stop leak, if it's possible to do so without risk. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Finish

cleaning by rinsing with water contaminated surface. Dispose via a licensed waste disposal contractor.

7. HANDLING AND STORAGE

Precautions for safe handling

: This product should not be mixed with acids since evolution of toxic and flammable hydrogen sulfide gas could result. This precaution does not, of course, apply to addition of this reagent to flotation pulps in amounts customarily used for flotation. Use only in well ventilated area. Avoid all contact with skin, eyes and clothing. Do not breathe vapors, mists or aerosols. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep in the workplace only the quantities necessary for the work being performed. Keep containers tightly closed when not used. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toilet articles. Remove contaminated clothing and wash before reuse.

Conditions for safe storage

: Store tightly close and in properly labelled containers in a cool, dry and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from acids and from incompatible materials (see section 10). Keep away from direct sunlight and heat.

Storage temperature

:

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Immediately Dangerous to Life or Health

Isopropyl alcohol : 2000 ppm.

Límites de exposición

Isopropyl alcohol	: STEL	400 ppm	ACGIH, BC, ON
		500 ppm	1230 mg/m ³ RSST
	TWA (8h)	200 ppm	ACGIH, BC, ON
		400 ppm	980 mg/m ³ OSHA
		400 ppm	983 mg/m ³ RSST

Potassium hydroxide : Maximum 2 mg/m³ ACGIH, BC, NIOSH, ON, RSST

Exposure controls

Appropriate engineering controls: Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapors, mists, aerosols or dust below their respective occupational exposure limits.

Respiratory protection

: Respiratory protection is not required in normal use. Respiratory protection equipment (PPE) must be selected, fitted, maintained and inspected in accordance with regulations and CSA Standard Z 94.4 and approved by NIOSH / MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit: wear a half mask respirator with appropriate cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with appropriate cartridges and P100 filters.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. Wear an apron or long-sleeve protective coverall suit.

Eye / face protection

: Wear chemical splash goggles. If risk of contact with eyes or the face, wear a face shield.

Hands

: Wear nitrile or neoprene gloves. Chemical-resistant, impervious gloves should be worn at all times when handling this chemical product. Before using, user should confirm impermeability. Discard gloves that show tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.

Other protective equipment

: Wear safety shoes. Wear rubber boots to clean up a spill.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid	Flammability limits (% by vol.)	: N/Av
Color	: Ambar to light brown	Flash point	: 90°C (194°F) SETA
Odor	: Slight sulfur odor	Auto-ignition temperature	: 200°C (392°F)
Odor threshold	: N/Av	Sensibility to electrostatic charge	: Yes
pH	: 10-11	Sensibility to sparks/friction	: No
Melting/Freezing point	: 4°C (24.8°F)	Vapor density (Air = 1)	: 0.6 a 0.7
Boiling point/range	: 103°C (217.4°F)	Relative density (Water = 1)	: 1.01 kg/L @ 25°C (77°F)
Solubility in water	: Partially soluble	Partition coefficient (n-octanol/water)	: N/Av
Evaporation rate (BuAc = 1)	: N/Av	Decomposition temperature	: 103°C (217.4°F)
Vapor pressure	: 2.3kPa (17.3 mm Hg) @ 20°C	Viscosity	: N/Av
Volatiles (% by weight)	: 50%	Molecular mass	: N/Av
Flammability (solid, gas)	: Combustible		

10. STABILITY AND REACTIVITY

Reactivity : May release hydrogen sulfide in contact with acids.
Chemical stability : Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations) : Hazardous polymerization will not occur.
Conditions to avoid : Avoid contact with incompatible materials.
Incompatible materials : Strong acids, strong bases, strong oxidizing agents (such as nitric acid, perchloric acid, peroxides, chlorates and perchlorates).
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

Toxicological data

Chemical name	LC ₅₀ (Inhalation, rat)	LD ₅₀ / mg/kg	
		(Oral, rat)	(Dermal, rabbit)
Ethyl Isopropyl Thionocarbamate	20 mg/l/4h	568	>2000
Isopropyl alcohol	66.1 mg/l/4h	5045	12870
Propylene Glycol Monomethyl Ether	No disponible	46510	>19100
Propilenglicol	No disponible	9760	>2000
Potassium hydroxide	No disponible	273	No disponible

Likely routes of exposure

Skin : Yes
Eye : Yes
Inhalation : Yes
Ingestion : Yes

Potential Health Effects:

Signs and symptoms of delayed, immediate and chronic effects:

Skin : May cause skin irritation and burns. The sodium O,O-alkyl dithiophosphate family compound is corrosive to rabbit skin, causing edema, erythema, tissue sloughing and necrosis (OECD 404).
Eye : May cause severe eye irritation or eye damage.
Inhalation : Inhalation of vapors/mists can cause burns to nose, throat and respiratory tract.
Ingestion : May cause burns to mouth, throat and stomach.
Sensitization to material : Ingredients present at levels greater than or equal to 0.1% of this product are skin or respiratory sensitizers.
IRAC/NTP Classification : No ingredients listed
Carcinogenicity : Ingredients present at levels greater than or equal to 0.1% of this product are not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA.
Mutagenicity : Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effect.
Reproductive Effects : Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause effects on reproduction.
Specific target organ effects – single exposure : No target organ is listed.
Specific target organ effects – repeated exposure : No target organ is listed.
Other information : The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.

12. ECOLOGICAL INFORMATION



- Ecotoxicity** :
- Fish - Danio rerio LD₅₀ 63 mg/L; 96 h (Ethyl Isopropyl Thionocarbamate) OCDE 203
 - Daphnia magna EC₅₀ 60 mg/L; 48 h (Ethyl Isopropyl Thionocarbamate) OCDE 202
 - Pseudokirchnerilla subcapitata EC₅₀ 20.8 mg/L; 72 h (Ethyl Isopropyl Thionocarbamate) OCDE 201
 - Pimephales promelas LC₅₀ 9640 mg/L; 96 h (Isopropyl Alcohol)
- Persistence** : No information available for this product. May be persistent in aquatic environment.
- Degradability** : Ethyl Isopropyl Thionocarbamate is not biodegradable (2.1%) under test conditions within a 28 day exposure period (OECD Guide 301D). However, it was found that it does not hydrolyze at pH 4 to 9 and has a half-life of less than one year at 25 ° C (OECD Guide 111). Isopropyl alcohol and n-propanol are soluble in water and evaporate quickly in air. There is no partition in the ground.
- Bioaccumulation potential** : No information available for this product. The sodium O,O-alkyl dithiophosphate family compound has a low potential to bioaccumulate.
- Mobility in soil** : Based on the high solubility in water, a high mobility in soil is to be expected.
- Other adverse environmental effects** : Toxic effect on aquatic organisms due to pH change. This chemical does not deplete the ozone layer.

13. DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Important! Prevent waste generation. Use in full. DO NOT throw residual to sewer, streams, sewers or drinking water supply. Residues and empty containers must be considered as hazardous waste. Return empty container properly labeled to supplier or everywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.

14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
DOT	NA1719	CORROSIVE LIQUID, N.O.S. (ISOPROPANOL)			
Additional Information	This material is not considered a marine pollutant. Not regulated in containers holding less than 120 gallons (450 L) Permit is required for transportation with appropriate placards posted on the vehicle.				
TDG	Not regulated				Corrosive
Additional Information	This material is considered a marine pollutant				
IMO/MDG	Not regulated				Corrosive
Additional Information					
IATA	Not regulated				Corrosive
Additional Information	This material is considered a marine pollutant				

15 - REGULATORY INFORMATION

- US Federal Information:**
- Toxic Substance Control Act (TSCA)
All ingredients are listed in the TSCA Inventory or otherwise comply with TSCA requirements.
 - EPCRA Section 313 Toxic Chemicals:

Sodium hydroxide (CAS no 1310-73-2).
 - CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act):



- Sodium hydroxide (CAS no 1310-73-2).
- EPCRA Section 302/304 Extremely Hazardous Substances:
No material is listed.
- Clean Water Act (CWA) 311 Hazardous Substances:
Sodium hydroxide (CAS no 1310-73-2).
- Clean Water Act (CWA) Priority Pollutants:
No material is listed.
- Clean Air Act (CAA) 111:
No material is listed.
- Clean Air Act (CAA 112b) HON - Hazardous Organic National Emission Air Pollutants:
No material is listed.
- Clean Air Act (CAA 112b) HAP - Hazardous Air Pollutants:
No material is listed.
- CAA 112(r) Regulated Chemicals for Accidental Release Prevention:
No material is listed.
- California Proposition 65:
No material is listed.

Canadian Information:

- Canada DSL and NDSL:
All ingredients are listed in the Domestic Substances List (DSL).
- Canadian National Pollutant Release Inventory Substances (NPRI):
No material is listed.

WHMIS 1988:

Class E : Corrosive material

16. OTHER INFORMATION

Other special considerations for handling : Provide adequate information, instruction and training for operators.

Prepared by: Flottec, LLC

Revised by:

REASON FOR REVISION:

DISCLAIMER

The above information is believed to be accurate and represents the best information currently available to us. However, we make no warrantee of merchantability or any other warrant, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular uses.

END OF DOCUMENT